

Installation manual Model: BMW 5ER

Skid plate for: AT case

Years: 1995 - 2003 Engine type: 2,0; 2,3; 2,5; 2,8

Engine bay and transmission elements skid plate has been designed and manufactured by LLC Metalloproduktsia. Product conforms to TOR 4591-001-25888788-2006 requirements. Product design is protected by model copyright certificates №89059, 15980, 15981, 15982, 15983, Patented in Russian Federation.

Body type: E39

APPLICATION:

 $Protection \ of engine \ bay \ and \ transmission \ elements \ from \ mechanical \ deformation.$

Protection of engine bay and transmission elements from dust and damp.

INSTALLATION:

Engine bay and transmission elements skid plate has been designed particularly for a certain vehicle. It should be mounted according to the producer's installation instruction by a dedicated dealer or on certified service stations. The skid plate is fixed to regular apertures located on vehicle's body load-bearing elements. In case of correct installation the skid plate should not interfere with any vehicle's units and components.

INSTALLATION MANUAL:

- 1. The skid plate should be installed together with the skid plate for engine bay 03.0294.
- 2. Fix the skid plate's beam to the car's load bearing elements with bolts M 8x30 -(A).
- 3. In front fix the skid plate to the already installed skid plate for engine bay; fix into mounted beam with bolts M 8x20 in rear.
- 4. Tighten all screw joints.

OPERATING CONDITIONS:

Engine bay and transmission elements skid plate has been designed to operate in conditions specified by vehicle's producer. Cases of crush or driving into obstacles at a speed should be excluded during exploitation. In case of head-on crush it is necessary to assure in absence of damages of vehicle's components and units and availability of roadworthiness on certified service stations.

WARRANTY:

Warranty period - 24 months.


WARRANTY TERMS:

The skid plate should be installed on a vehicle with undamaged body and load-bearing elements (vehicle, which hads never been involved in road traffic accident);


There are no mechanical damages of the skid plate resulting from head-on crush. All requirements to skid plate installation should be satisfied;

There are no mechanical damages of powder coating.

Producer does not bear liability for damages caused to the vehicle, health and life of people in case of installation and exploitation terms violation. Producer has a right to introduce changes into the skid plate construction.



Article: 03.0404



LIST OF PARTS

LIOT OF TAIRTO					
NO.	NAME	QTY.			
1	Rear beam	1			
2	Bolt M 8x20	5			
3	Bolt M 8x30	2			
4	Washer 8	7			

Thread	M6x1.0	M8x1.25	M10x1.5	M12x1.75
Tightening torque	9.8 Nm	24.0 Nm	47.0 Nm	81.0 Nm